

Pour démarrer depuis le memoire flash NAND (plus besoin de SDCARD point faible du Raspberry)

How to boot from emmc with SD data

STEP 1. boot from SD

1a. bpi-copy xxx.img.zip #burn to emmc ;

1b. bpi-bootsel BPI_M2U_720P-emmc.img.gz /dev/mmcblk1 #auto download from github and burn to emmc;

1c. bpi-bootsel BPI-cleanboot-8k.img.gz /dev/mmcblk0 #auto download from github and burn to SD;

STEP 2. boot from emmc

2a. poweroff

2b, remove SD card

2c. poweron

2d. insert SD card

2e. fdisk /dev/mmcblk1 and mkfs -t ext4 /dev/mmcblk1p1

Derniere image https://drive.google.com/file/d/1aoB8mGwSveNztB-EO_fBKLOr-GdzcMNV/view

Pour booter sur un sata Formatter le disque Monter le disque

```
sudo mount /dev/sda /media sudo rsync -ax / /media (dir a filtrer?) mkdir /tmp/boot mount /dev/mmcblk0p1 /tmp/boot nano /tmp/boot/./720/uEnv.txt remplacer /dev/mmcblk0p2 par /dev/sda
```

From:

<https://mistert.freeboxos.fr/dokuwiki/> - Wiki de Sébastien TACK

Permanent link:

https://mistert.freeboxos.fr/dokuwiki/doku.php?id=14_-_bananapi_tests&rev=1579978884

Last update: **2020/09/26 15:15**

